SEM

Printing date 10/22/2018 Version number 15 Reviewed on 10/22/2018

1 Identification

- · Product identifier
- · Trade name: 15011-15596 Color Coat RTS
- · Article number:

15011, 15014, 15015, 15016, 15041, 15081, 15084, 15086, 15091, 15101, 15111, 15275, 15305, 15311, 15501, 15504, 15506, 15511, 15514, 15516, 15521, 15524, 15526, 15531, 15534, 15536, 15541, 15544, 15545, 15546, 15556, 15561, 15564, 15566, 15576, 15581, 15584, 15586, 15591, 15594, 15596, 1501-DR

- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids - Category 2 H225 Highly flammable liquid and vapour.



GHS08 Health hazard

Carcinogenicity – Category 2 H351 Suspected of causing cancer.

Reproductive Toxicity - Category 2 H361 Suspected of damaging fertility or the unborn

child.

Specific Target Organ Toxicity - Repeated Exposure - H373 May cause damage to organs through Category 2 prolonged or repeated exposure.



GHS07

Skin Irritation - Category 2 H315 Causes skin irritation.

Eye Irritation - Category 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure - H336 May cause drowsiness or dizziness.

Category 3

- · Label elements
- $\cdot \textit{GHS label elements} \ \textit{The product is classified and labeled according to the Globally Harmonized System (GHS)}.$

(Contd. on page 2)

Printing date 10/22/2018 Version number 15 Reviewed on 10/22/2018

Trade name: 15011-15596 Color Coat RTS

(Contd. of page 1)

· Hazard pictograms







· Signal word Danger

· Hazard-determining components of labeling:

toluene

butanone

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P201	Obtain special	instructions	hafara usa
P201	Obtain speciai	instructions	peтore use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P240 Ground and bond container and receiving equipment.

P241 *Use explosion-proof [electrical/ventilating/lighting] equipment.*

P242 *Use non-sparking tools.*

P243 Take actions to prevent static discharges.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 *In case of fire: Use for extinction: CO2, powder or water spray.* P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 3)

(Contd. of page 2)

Printing date 10/22/2018 Version number 15 Reviewed on 10/22/2018

Trade name: 15011-15596 Color Coat RTS

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Fire = 3

3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:				
108-88-3		60-80% w/w *		
78-93-3	butanone	≥5-<10% w/w *		
108-65-6	2-methoxy-1-methylethyl acetate	1-5% w/w *		
2807-30-9	2-(propyloxy)ethanol	1-5% w/w *		
100-41-4	ethylbenzene	0.1-1% w/w *		

* Actual concentration ranges are withheld as a trade secret.

4 First aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)

SEM

Printing date 10/22/2018 Version number 15 Reviewed on 10/22/2018

Trade name: 15011-15596 Color Coat RTS

(Contd. of page 3)

· Special hazards arising from the substance or mixture

- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)

- CA

Printing date 10/22/2018 Version number 15 Reviewed on 10/22/2018

Trade name: 15011-15596 Color Coat RTS

(Contd. of page 4)

	· Control parameters					
	· Coi	nponents with limit values that require monitoring at the workplace:				
ı	108	3-88-3 toluene				
ı	EL	Long-term value: 20 ppm				
		R				
	EV	Long-term value: 20 ppm				
	<i>78-</i> .	93-3 butanone				
Ī	EL	Short-term value: 100 ppm				
		Long-term value: 50 ppm				
	EV	Short-term value: 885 mg/m³, 300 ppm				
		Long-term value: 590 mg/m³, 200 ppm				
	108	3-65-6 2-methoxy-1-methylethyl acetate				
	EL	Short-term value: 75 ppm				
		Long-term value: 50 ppm				
	EV	Long-term value: 270 mg/m³, 50 ppm				
	280	7-30-9 2-(propyloxy)ethanol				
	EV	Long-term value: 110 mg/m³, 25 ppm				
		Skin				
	100	0-41-4 ethylbenzene				
	EL	Long-term value: 20 ppm				
		IARC 2B				
	EV	Short-term value: 540 mg/m³, 125 ppm				

- Long-term value: 435 mg/m³, 100 ppm · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)



Printing date 10/22/2018 Version number 15 Reviewed on 10/22/2018

Trade name: 15011-15596 Color Coat RTS

(Contd. of page 5)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Information on basic physical and	chemical properties
General Information	p. op o
Appearance:	
Form:	Liquid
Color:	According to product specification
· Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	79 °C
Flash point:	-4 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	514 °C
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7 Vol %
Vapor pressure at 20 °C:	29 hPa
Density at 20 °C:	$0.91393 \ g/cm^3$
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 7)



Printing date 10/22/2018 Version number 15 Reviewed on 10/22/2018

Trade name: 15011-15596 Color Coat RTS

 Solvent content:
 (Contd. of page 6)

 Organic solvents:
 84.7 %

 Water:
 0.0 %

 VOC content:
 84.72 %

 774.3 g/l / 6.46 lb/gal

 Solids content:
 15.3 %

 • Other information
 No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 v	· LD/LC50 values that are relevant for classification:			
108-88-3 te	oluene			
Oral	LD50	5,000 mg/kg (rat)		
Dermal	LD50	12,124 mg/kg (rabbit)		
Inhalative	LC50/4 h	5,320 mg/l (mouse)		

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Inte	ernational Agency for Research on Cancer)	
108-88-3	toluene	3
1330-20-7	xylene	3
	ethylbenzene	2B
1333-86-4	Carbon black	2 <i>B</i>
· NTP (Natio	onal Toxicology Program)	
None of the	e ingredients is listed.	

- CA

SEM

Printing date 10/22/2018 Version number 15 Reviewed on 10/22/2018

Trade name: 15011-15596 Color Coat RTS

(Contd. of page 7)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · DOT, TDG, IMDG, IATA UN1263
- · UN proper shipping name
- · **DOT** Pain
- TDG 1263 Paint, special provision 640D
- · IMDG, IATA PAINT
- · Transport hazard class(es)
- $\cdot DOT$



- · Class 3 Flammable liquids
- · Label

(Contd. on page 9)



Printing date 10/22/2018 Version number 15 Reviewed on 10/22/2018

Trade name: 15011-15596 Color Coat RTS

(Contd. of page 8) · TDG, IMDG, IATA 3 Flammable liquids · Class · Label · Packing group · DOT, TDG, IMDG, IATA II· Environmental hazards: · Marine pollutant: · Special precautions for user Warning: Flammable liquids · EMS Number: F-E,S-E· Stowage Category · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: $\cdot DOT$ On passenger aircraft/rail: 5 L · Quantity limitations On cargo aircraft only: 60 L $\cdot TDG$ · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · IMDG 5L· Limited quantities (LQ) · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · UN "Model Regulation": UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

· Section 51.	5 (Specific toxic chemical usings):			
108-88-3	toluene			
	Acrylic Resin			
1330-20-7	xylene			
67-56-1	methanol			
	108-88-3 78-93-3 1330-20-7	108-88-3 toluene Acrylic Resin 1330-20-7 xylene 67-56-1 methanol	108-88-3 toluene Acrylic Resin 78-93-3 butanone 1330-20-7 xylene	108-88-3 toluene Acrylic Resin 78-93-3 butanone 1330-20-7 xylene

(Contd. on page 10)

Sheet Schedule 1

Printing date 10/22/2018 Version number 15 Reviewed on 10/22/2018

Trade name: 15011-15596 Color Coat RTS

100-41-4	(Contd. of page 4) (Contd. of pa
	ic Substances Control Act):
108-88-3	
78-93-3	butanone
51274-00-1	YELLOW IRON OXIDE
108-65-6	2-methoxy-1-methylethyl acetate
2807-30-9	2-(propyloxy)ethanol
1330-20-7	xylene
67-56-1	methanol
100-41-4	ethylbenzene
1333-86-4	Carbon black
68911-87-5	montmorilontie clay complex
61791-55-7	Amines, N-tallow alkyltrimethylenedi-
78-83-1	butanol
111-66-0	oct-1-ene
7732-18-5	water
Canadian sı	ubstance listings:
Canadian D	Oomestic Substances List (DSL)
108-88-3	toluene
<i>78-93-3</i>	butanone
51274-00-1	YELLOW IRON OXIDE
108-65-6	2-methoxy-1-methylethyl acetate
2807-30-9	2-(propyloxy)ethanol
1330-20-7	xylene
	methanol
100-41-4	ethylbenzene
1333-86-4	Carbon black
	montmorilontie clay complex
61791-55-7	Amines, N-tallow alkyltrimethylenedi-
78-83-1	butanol
111-66-0	oct-1-ene
7732-18-5	water
Canadian II	ngredient Disclosure list (limit 0.1%)
100-41-4 et	hylbenzene
Canadian II	ngredient Disclosure list (limit 1%)
108-88-3 to	luene
78-93-3 bi	utanone

Printing date 10/22/2018 Version number 15 Reviewed on 10/22/2018

Trade name: 15011-15596 Color Coat RTS

(Contd. of page 10)

· Hazard pictograms







· **Signal word** Danger

· Hazard-determining components of labeling:

toluene

butanone

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P201	Obtain special	instructions	before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P240 Ground and bond container and receiving equipment.

P241 *Use explosion-proof [electrical/ventilating/lighting] equipment.*

P242 *Use non-sparking tools.*

P243 Take actions to prevent static discharges.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 *In case of fire: Use for extinction: CO2, powder or water spray.* P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 12)

Safety Data Sheet according to HPR, Schedule 1

SEM

Printing date 10/22/2018 Version number 15 Reviewed on 10/22/2018

Trade name: 15011-15596 Color Coat RTS

(Contd. of page 11)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner (rjoiner@semproducts.com)
- · Date of the latest revision of the safety data sheet 10/22/2018 / 14
- · Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

* Data compared to the previous version altered.

CA