Printing date 07/31/2018

Version number 14

Reviewed on 07/31/2018

1 Identification

- · Product identifier
- · Trade name: 38253 Premium Guide Coat
- · Article number: 38253
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225
- · Information department:

cust_care@semproducts.com: SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730: phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Aerosols - Category 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if

heated.



GHS04 Gas cylinder

Gases Under Pressure - Compressed Gas H280 Contains gas under pressure; may

explode if heated.



GHS08 Health hazard

Reproductive Toxicity - Category 2 H361 Suspected of damaging fertility or the

unborn child.

Specific Target Organ Toxicity - Repeated Exposure -H373 May cause damage to organs through

Category 2 prolonged or repeated exposure.



GHS07

Skin Irritation - Category 2	H315	Causes skin irritation.
Eye Irritation - Category 2A	H319	Causes serious eye irritation.
Specific Target Organ Toxicity - Single Exposure -	H336	May cause drowsiness or dizziness.
Category 3		

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)

Printing date 07/31/2018 Version number 14 Reviewed on 07/31/2018

Trade name: 38253 Premium Guide Coat

(Contd. of page 1)

· Hazard pictograms









· Signal word Danger

· Hazard-determining components of labeling:

acetone

toluene

· Hazard statements

H222-H229 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation. H319 Causes serious eve irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P410+P412

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

(Contd. on page 3)

(Contd. of page 2)



Printing date 07/31/2018 Version number 14 Reviewed on 07/31/2018

Trade name: 38253 Premium Guide Coat

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 4 Reactivity = 3

· HMIS-ratings (scale 0 - 4)



2 Health = 24 Fire = 4

REACTIVITY 3 Reactivity = 3

*

3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:		
67-64-1	acetone	30-60% w/w *
68476-86-8	Petroleum gases, liquefied, sweetened	10-30% w/w *
14807-96-6	Talc	3-7% w/w *
108-88-3	toluene	1-5% w/w *

^{*} Actual concentration ranges are withheld as a trade secret.

*

4 First aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

*

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

Printing date 07/31/2018 Version number 14 Reviewed on 07/31/2018

Trade name: 38253 Premium Guide Coat

(Contd. of page 3)

· Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

· Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

67-64-1 acetone

EL Short-term value: 500 ppm Long-term value: 250 ppm

(Contd. on page 5)

Safety Data Sheet according to HPR, Schedule 1

SEM

Printing date 07/31/2018 Version number 14 Reviewed on 07/31/2018

Trade name: 38253 Premium Guide Coat

(Contd. of page 4)

EV Short-term value: 750 ppm Long-term value: 500 ppm

108-88-3 toluene

EL Long-term value: 20 ppm

R

EV Long-term value: 20 ppm

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol
Color: Black

(Contd. on page 6)

et SEM

Printing date 07/31/2018 Version number 14 Reviewed on 07/31/2018

Trade name: 38253 Premium Guide Coat

	(Contd. of pag
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55.8-56.6 °C
Flash point:	-103 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	365 °C
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	1.5 Vol %
Upper:	13 Vol %
Vapor pressure at 20 °C:	8,300 hPa
Density at 20 °C:	0.75945 g/cm^3
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	t er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	87.5 %
Water:	0.0 %
VOC content:	29.53 %
	507.0 g/l / 4.23 lb/gal
Solids content:	12.5 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 7)



Printing date 07/31/2018 Version number 14 Reviewed on 07/31/2018

Trade name: 38253 Premium Guide Coat

(Contd. of page 6)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
67-64-1 ac	67-64-1 acetone		
Oral	LD50	5,800 mg/kg (rat)	
Dermal	<i>LD50</i>	20,000 mg/kg (rabbit)	
108-88-3 t	108-88-3 toluene		
Oral	LD50	5,000 mg/kg (rat)	
Dermal	<i>LD50</i>	12,124 mg/kg (rabbit)	
Inhalative	LC50/4 h	5,320 mg/l (mouse)	

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Inter	national Agency for Research on Cancer)	
14807-96-6	Talc	3
108-88-3	toluene	3
1333-86-4	Carbon black	2B
1330-20-7	xylene	3
	ethylbenzene	2 <i>B</i>
14808-60-7	Quartz (SiO2)	1
· NTP (Natio	nal Toxicology Program)	
14808-60-7	Quartz (SiO2)	K

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

(Contd. on page 8)

Safety Data Sheet according to HPR, Schedule 1



Printing date 07/31/2018 Version number 14 Reviewed on 07/31/2018

Trade name: 38253 Premium Guide Coat

(Contd. of page 7)

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

. IIN_Numh	014

· DOT, TDG, IMDG, IATA UN1950

· UN proper shipping name

 $\cdot DOT$ Aerosols, flammable $\cdot TDG$ 1950 Aerosols \cdot IMDG **AEROSOLS**

 \cdot IATA AEROSOLS, flammable

- · Transport hazard class(es)
- $\cdot DOT$



· Class 2.1

2.1 · Label

· TDG (Transport dangerous goods):



· Class 2 5F Gases 2.1

· Label

· IMDG, IATA



· Class 2.1

· Label 2.1

(Contd. on page 9)

Safety Data Sheet according to HPR, Schedule 1

Printing date 07/31/2018 Version number 14 Reviewed on 07/31/2018

Trade name: 38253 Premium Guide Coat

	(Contd. of page
· Packing group · DOT, TDG, IMDG, IATA	Void
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · EMS Number: · Stowage Code	Warning: Gases F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Catego A. For AEROSOLS with a capacity above 1 litre: Category B. Fo WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litr. Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litr. Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Transport in bulk according to Annex . MARPOL73/78 and the IBC Code	II of Not applicable.
· Transport/Additional information:	
· DOT · Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
· Remarks	ORM-D 49CFR 173.150,156,306
· TDG · Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information

- $\cdot \textit{Safety, health and environmental regulations/legislation specific for the substance or \textit{mixture}}$
- $\cdot \textit{Sara}$

· Section 355 (extremely hazardous substances):	
None of the ingredient is listed.	

· Section 313 (Specific toxic chemical listings):	
14807-96-6	
108-88-3	
1330-20-7	
	methanol
100-41-4	ethylbenzene

(Contd. on page 10)

Printing date 07/31/2018 Version number 14 Reviewed on 07/31/2018

Trade name: 38253 Premium Guide Coat

67-64-1 acetone 108-88-3 toluene

(Contd. of page 9) · TSCA (Toxic Substances Control Act): 67-64-1 acetone 14807-96-6 Talc 1317-65-3 GROUND CALCIUM CARBONATE 108-88-3 toluene 16883-83-3 benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate 1333-86-4 Carbon black 68911-87-5 montmorilontie clay complex 123-86-4 n-butyl acetate 1330-20-7 xylene 67-56-1 methanol 100-41-4 ethylbenzene 78-83-1 butanol 14808-60-7 Quartz (SiO2) 7732-18-5 water · Canadian substance listings: · Canadian Domestic Substances List (DSL) 67-64-1 acetone 68476-86-8 Petroleum gases, liquefied, sweetened 14807-96-6 Talc 108-88-3 toluene 16883-83-3 benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate 1333-86-4 Carbon black 68911-87-5 montmorilontie clay complex 123-86-4 n-butyl acetate 1330-20-7 xylene 67-56-1 methanol 100-41-4 ethylbenzene 78-83-1 butanol 14808-60-7 Quartz (SiO2) 7732-18-5 water · Canadian Ingredient Disclosure list (limit 0.1%) None of the ingredients is listed. · Canadian Ingredient Disclosure list (limit 1%)

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 11)



Printing date 07/31/2018 Version number 14 Reviewed on 07/31/2018

Trade name: 38253 Premium Guide Coat

(Contd. of page 10)

· Hazard pictograms









· Signal word Danger

· Hazard-determining components of labeling:

acetone

toluene

· Hazard statements

H222-H229 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation. H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 *If eye irritation persists: Get medical advice/attention.*

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P410+P412

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Safety Data Sheet according to HPR, Schedule 1

SEM

Printing date 07/31/2018 Version number 14 Reviewed on 07/31/2018

Trade name: 38253 Premium Guide Coat

(Contd. of page 11)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner (rjoiner@semproducts.com)
- Date of the latest revision of the safety data sheet 07/31/2018 / 13
- · Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

* Data compared to the previous version altered.

CΔ