

### 1 Identification

- · Product identifier
- · Trade name: 39304 39308 Rust Seal
- · Article number: 39304, 39308
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc.

1685 Overview Drive

Rock Hill, SC 29730

803 207 8225

· Information department:

cust\_care@semproducts.com: SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730: phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

## 2 Hazard identification

- · Classification of the substance or mixture According to GHS, the product is not classified.
- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0Fire = 1

REACTIVITY  $\boxed{0}$  Reactivity = 0

### 3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous	components:
-------------	-------------

g		
57-55-6	Methyl glycol	1-5% w/w
107-21-1	ethanediol	1-5% w/w

(Contd. on page 2)

Trade name: 39304 39308 Rust Seal

(Contd. of page 1)

\*

### 4 First aid measures

- · Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# 5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

.

### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

\*

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- $\cdot$  *Specific end use*(s) *No further relevant information available.*

'A -

Trade name: 39304 39308 Rust Seal

(Contd. of page 2)

# 8 Exposure controls/ Personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

#### 57-55-6 Methyl glycol

EV Long-term value: 155\* 10\*\* mg/m³, 50\* ppm \*vapour and aerosol; \*\*aerosol only

#### 107-21-1 ethanediol

EL Short-term value: 20\*\* mg/m³ Long-term value: 10\*\* mg/m³

Ceiling limit value: 100\* mg/m³, 50\*\*\* ppm

\*Aerosol; \*\*Particulate; \*\*\*Vapour

- EV Ceiling limit value: 100 mg/m<sup>3</sup>
- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

- · Breathing equipment: Not required.
- · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

*Color:* According to product specification

Odor: CharacteristicOdor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

(Contd. on page 4)

according to HPR, Schedule 1

Reviewed on 10/27/2015

Trade name: 39304 39308 Rust Seal

Printing date 03/21/2018

		(Contd. of page
Boiling point/Boiling range:	100 °C	
Flash point:	110 °C	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C:	23 hPa	
Density at 20 °C:	$1.06217 \text{ g/cm}^3$	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa	ter): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	2.7 %	
Water:	35.2 %	
VOC content:	2.68 %	
	45.5 g/l / 0.38 lb/gl	
Solids content:	58.6 %	
Other information	No further relevant information available.	

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

CA.

Trade name: 39304 39308 Rust Seal

(Contd. of page 4)

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Smaller quantities can be disposed of with household waste.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

CΔ

(Contd. on page 6)

Trade name: 39304 39308 Rust Seal

(Contd. of page 5)

UN-Number DOT, TDG, ADN, IMDG, IATA	Void	
UN proper shipping name DOT, TDG, ADN, IMDG, IATA	Void	
Transport hazard class(es)		
DOT, TDG, ADN, IMDG, IATA Class	Void	
Packing group DOT, TDG, IMDG, IATA	Void	
Environmental hazards: Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	<b>II of</b> Not applicable.	
UN "Model Regulation":	Void	

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section 355 (extremely hazardous substances):		
None of the	None of the ingredient is listed.	
· Section 313 (Specific toxic chemical listings):		
A	Acrylic Resin	
107-21-1 e	thanediol	
64-18-6 fe	64-18-6 formic acid	
· TSCA (Toxic Substances Control Act):		
57-55-6	Methyl glycol	
107-21-1	ethanediol	
64-18-6	formic acid	
149-91-7	3,4,5-trihydroxybenzoic acid	
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	
11138-66-2	Xanthan gum	
9003-11-6	Polyoxypropylene-polyoxyethylene Block Copolymer	
7732-18-5	water	

· Canadian substance listings:

· Canadian D	omestic Substances List (DSL)		
57-55-6	Methyl glycol		
107-21-1	ethanediol		
64-18-6	formic acid		

(Contd. on page 7)

SEM

Printing date 03/21/2018 Reviewed on 10/27/2015

Trade name: 39304 39308 Rust Seal

	(Contd. of page 6)		
	3,4,5-trihydroxybenzoic acid		
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol		
11138-66-2	Xanthan gum		
9003-11-6	Polyoxypropylene-polyoxyethylene Block Copolymer		
7732-18-5	water		
· Canadian I	· Canadian Ingredient Disclosure list (limit 0.1%)		
None of the	None of the ingredients is listed.		
· Canadian I	· Canadian Ingredient Disclosure list (limit 1%)		
57-55-6 M	lethyl glycol		
107-21-1 et	thanediol		
· GHS label e	· GHS label elements Void		

#### \_\_\_\_\_

Hazard pictograms Void
Signal word Void
Hazard statements Void

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

- · Contact: Rita Joiner (rjoiner@semproducts.com)
- · Date of preparation / last revision 03/21/2018 / 7
- · Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

 $NFPA: National\ Fire\ Protection\ Association\ (USA)$ 

 ${\it HMIS: Hazardous\ Materials\ Identification\ System\ (USA)}$ 

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

\* \* Data compared to the previous version altered.

CA -