

1 Identification

- **Product identifier**
- **Trade name:** 39492 No Swell Plastic Panel Filler (w/HRDNR)
- **Article number:** 39492
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

styrene

(Contd. on page 2)

USA

Trade name: 39492 No Swell Plastic Panel Filler (w/HRDNR)

(Contd. of page 1)

Talc

BISPHENOL A DIGLYCIDAL METHACRYLATE

· **Hazard statements**

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



(Contd. on page 3)



Trade name: 39492 No Swell Plastic Panel Filler (w/HRDNR)

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**
Mixture: consisting of the following components.
Weight percentages

· **Dangerous components:**

14807-96-6	Talc	40-60%
100-42-5	styrene	13-30%
1565-94-2	BISPHENOL A DIGLYCIDAL METHACRYLATE	10-13%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

**Trade name: 39492 No Swell Plastic Panel Filler (w/HRDNR)**

(Contd. of page 3)

Ensure adequate ventilation.

• **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

• **Protective Action Criteria for Chemicals**• **PAC-1:**

100-42-5	styrene	20 ppm
13463-67-7	titanium dioxide	30 mg/m ³
67-64-1	acetone	200 ppm
123-31-9	1,4-dihydroxybenzene	3 mg/m ³
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³

• **PAC-2:**

100-42-5	styrene	130 ppm
13463-67-7	titanium dioxide	330 mg/m ³
67-64-1	acetone	3200* ppm
123-31-9	1,4-dihydroxybenzene	20 mg/m ³
14808-60-7	Quartz (SiO ₂)	33 mg/m ³

• **PAC-3:**

100-42-5	styrene	1100* ppm
13463-67-7	titanium dioxide	2,000 mg/m ³
67-64-1	acetone	5700* ppm
123-31-9	1,4-dihydroxybenzene	120 mg/m ³
14808-60-7	Quartz (SiO ₂)	200 mg/m ³

* **7 Handling and storage**• **Handling:**• **Precautions for safe handling** No special measures required.• **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

• **Conditions for safe storage, including any incompatibilities**• **Storage:**• **Requirements to be met by storerooms and receptacles:** No special requirements.• **Information about storage in one common storage facility:** Not required.• **Further information about storage conditions:** Keep receptacle tightly sealed.• **Specific end use(s)** No further relevant information available.* **8 Exposure controls/personal protection**• **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

Trade name: 39492 No Swell Plastic Panel Filler (w/HRDNR)

(Contd. of page 4)

• **Control parameters**

• **Components with limit values that require monitoring at the workplace:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

100-42-5 styrene

PEL	Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs
REL	Short-term value: 425 mg/m ³ , 100 ppm Long-term value: 215 mg/m ³ , 50 ppm
TLV	Short-term value: 170 mg/m ³ , 40 ppm Long-term value: 85 mg/m ³ , 20 ppm BEI

• **Ingredients with biological limit values:**

100-42-5 styrene

BEI	400 mg/g creatinine Medium: urine Time: end of shift Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific)
	0.2 mg/L Medium: venous blood Time: end of shift Parameter: Styrene (semi-quantitative)

• **Additional information:** The lists that were valid during the creation were used as basis.

• **Exposure controls**

• **Personal protective equipment:**

• **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

• **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

• **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Trade name: 39492 No Swell Plastic Panel Filler (w/HRDNR)

(Contd. of page 5)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Liquid

Color:

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

145 °C

· **Flash point:**

31 °C

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

480 °C

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

· **Danger of explosion:**

In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower:

1.2 Vol %

Upper:

8.9 Vol %

· **Vapor pressure at 20 °C:**

6 hPa

· **Density at 20 °C:**

2.00628 g/cm³

· **Relative density**

Not determined.

· **Vapor density**

Not determined.

· **Evaporation rate**

Not determined.

· **Solubility in / Miscibility with**

Water:

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic:

Not determined.

Kinematic:

Not determined.

(Contd. on page 7)



Trade name: 39492 No Swell Plastic Panel Filler (w/HRDNR)

(Contd. of page 6)

· Solvent content:	
Organic solvents:	13.3 %
Water:	0.0 %
VOC content:	13.18 %
· Solids content:	
	86.7 %
· Other information	
No further relevant information available.	

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

100-42-5 styrene

Oral	LD50	5,000 mg/kg (rat)
Inhalative	LC50/4 h	24 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc	3
100-42-5	styrene	2B
13463-67-7	titanium dioxide	2B
	RHEOLOGICAL ADDITIVE	2A <1% 14808-60-7
123-31-9	1,4-dihydroxybenzene	3
14808-60-7	Quartz (SiO ₂)	1

· **NTP (National Toxicology Program)**

100-42-5	styrene	R
14808-60-7	Quartz (SiO ₂)	K

(Contd. on page 8)



Printing date 03/14/2018

Reviewed on 06/20/2017

Trade name: 39492 No Swell Plastic Panel Filler (w/HRDNR)

(Contd. of page 7)

 · **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 1 (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|--|
| · UN-Number | UN1993 |
| · DOT, ADR, IMDG, IATA | |
| · UN proper shipping name | Flammable liquids, n.o.s. (Styrene monomer, stabilized) |
| · DOT | 1993 Flammable liquids, n.o.s. (Styrene monomer, stabilized) |
| · ADR | FLAMMABLE LIQUID, N.O.S. (STYRENE MONOMER, STABILIZED) |
| · IMDG, IATA | |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS



Printing date 03/14/2018

Reviewed on 06/20/2017

Trade name: 39492 No Swell Plastic Panel Filler (w/HRDNR)

(Contd. of page 8)

· Label	3
· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· Remarks	ORM-D 49CFR-173.150,156,306
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUIDS, N.O.S. (STYRENE MONOMER, STABILIZED), 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

123-31-9	1,4-dihydroxybenzene
----------	----------------------

· Section 313 (Specific toxic chemical listings):

14807-96-6	Talc
100-42-5	styrene

(Contd. on page 10)

USA

Trade name: 39492 No Swell Plastic Panel Filler (w/HRDNR)

(Contd. of page 9)

123-31-9	1,4-dihydroxybenzene
----------	----------------------

· **TSCA (Toxic Substances Control Act):**

14807-96-6	Talc
100-42-5	styrene
1565-94-2	BISPHENOL A DIGLYCIDAL METHACRYLATE
13463-67-7	titanium dioxide
1317-65-3	GROUND CALCIUM CARBONATE
67-64-1	acetone
123-31-9	1,4-dihydroxybenzene
14808-60-7	Quartz (SiO ₂)
7732-18-5	water

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-42-5	styrene
13463-67-7	titanium dioxide
14808-60-7	Quartz (SiO ₂)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogen categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
---------	---------	---

· **TLV (Threshold Limit Value established by ACGIH)**

14807-96-6	Talc	A4
100-42-5	styrene	A4
13463-67-7	titanium dioxide	A4
67-64-1	acetone	A4
123-31-9	1,4-dihydroxybenzene	A3
14808-60-7	Quartz (SiO ₂)	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
14808-60-7	Quartz (SiO ₂)

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

(Contd. on page 11)



Trade name: 39492 No Swell Plastic Panel Filler (w/HRDNR)

(Contd. of page 10)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

styrene

Talc

BISPHENOL A DIGLYCIDAL METHACRYLATE

· **Hazard statements**

H226 *Flammable liquid and vapor.*

H315 *Causes skin irritation.*

H319 *Causes serious eye irritation.*

H351 *Suspected of causing cancer.*

H361 *Suspected of damaging fertility or the unborn child.*

H335 *May cause respiratory irritation.*

H372 *Causes damage to the hearing organs through prolonged or repeated exposure.*

· **Precautionary statements**

P201 *Obtain special instructions before use.*

P202 *Do not handle until all safety precautions have been read and understood.*

P210 *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

P240 *Ground/bond container and receiving equipment.*

P241 *Use explosion-proof electrical/ventilating/lighting/equipment.*

P242 *Use only non-sparking tools.*

P243 *Take precautionary measures against static discharge.*

P260 *Do not breathe dust/fume/gas/mist/vapors/spray.*

P264 *Wash thoroughly after handling.*

P270 *Do not eat, drink or smoke when using this product.*

P271 *Use only outdoors or in a well-ventilated area.*

P280 *Wear protective gloves/protective clothing/eye protection/face protection.*

P303+P361+P353 *If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

P304+P340 *IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

P308+P313 *IF exposed or concerned: Get medical advice/attention.*

P312 *Call a poison center/doctor if you feel unwell.*

P321 *Specific treatment (see on this label).*

P314 *Get medical advice/attention if you feel unwell.*

P362+P364 *Take off contaminated clothing and wash it before reuse.*

P332+P313 *If skin irritation occurs: Get medical advice/attention.*

P337+P313 *If eye irritation persists: Get medical advice/attention.*

P370+P378 *In case of fire: Use for extinction: CO2, powder or water spray.*

P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*

P403+P235 *Store in a well-ventilated place. Keep cool.*

P405 *Store locked up.*

P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

(Contd. on page 12)



Printing date 03/14/2018

Reviewed on 06/20/2017

Trade name: 39492 No Swell Plastic Panel Filler (w/HRDNR)

(Contd. of page 11)

• **Contact:** Rita Joiner (rjoiner@semproducts.com)

• **Date of preparation / last revision** 03/14/2018 / 8

• **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

• *** Data compared to the previous version altered.**

USA