

## 1 Identification

- **Product identifier**
- **Trade name:** 40786 Brushable Copperweld Weld Thru Primer
- **Article number:** 40786
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
SEM Products Inc.  
1685 Overview Drive  
Rock Hill, SC 29730  
803 207 8225
- **Information department:**  
cust\_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

## 2 Hazard identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids - Category 2

H225 Highly flammable liquid and vapour.



GHS08 Health hazard

Germ Cell Mutagenicity - Category 1B

H340 May cause genetic defects.

Carcinogenicity - Category 1B

H350 May cause cancer.

Specific Target Organ Toxicity - Repeated Exposure - Category 2

H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard - Category 1

H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irritation - Category 2

H315 Causes skin irritation.

Eye Irritation - Category 2A

H319 Causes serious eye irritation.

Skin Sensitizer - Category 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure - Category 3

H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Trade name: 40786 Brushable Copperweld Weld Thru Primer

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

toluene  
ethylbenzene  
Solvent naphtha (petroleum), light aliph.  
n-butyl acetate  
2-butanone oxime

· **Hazard statements**

H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.  
P242 Use non-sparking tools.  
P243 Take actions to prevent static discharges.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P264 Wash thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310 If swallowed: Immediately call a poison center/doctor.  
P321 Specific treatment (see on this label).  
P331 Do NOT induce vomiting.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P312 Call a poison center/doctor if you feel unwell.  
P314 Get medical advice/attention if you feel unwell.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.

(Contd. on page 3)

**Trade name: 40786 Brushable Copperweld Weld Thru Primer**

(Contd. of page 2)

P370+P378      *In case of fire: Use for extinction: CO2, powder or water spray.*  
P403+P233      *Store in a well-ventilated place. Keep container tightly closed.*  
P403+P235      *Store in a well-ventilated place. Keep cool.*  
P405              *Store locked up.*  
P501              *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



### 3 Composition/Information on ingredients

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.  
Weight percentages

· **Dangerous components:**

123-86-4	n-butyl acetate	10-30% w/w
108-88-3	toluene	10-30% w/w
7440-50-8	copper	10-30% w/w
	EPOXY RESIN	≥10-≤13% w/w
7440-66-6	zinc powder -zinc dust	≥5-<10% w/w
1330-20-7	xylene	≥5-<10% w/w
12001-26-2	Mica	1-5% w/w
100-41-4	ethylbenzene	1-5% w/w
	BENTONITE	0.5-1.5% w/w
143860-04-2	3-ethyl-2-methyl-2-(3-methylbutyl)-1,3-oxazolidine	≥1-<1.5% w/w
90218-35-2	Dodecylbenzenesulfonic acid with 2-propanamine	0.5-1.5% w/w
96-29-7	2-butanone oxime	≥0.1-<1% w/w
64742-89-8	Solvent naphtha (petroleum), light aliph.	≥0.1-≤1% w/w
8052-41-3	Stoddard solvent	≥0.1-≤1% w/w

### 4 First aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 4)



**Trade name: 40786 Brushable Copperweld Weld Thru Primer**

(Contd. of page 3)

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
No special measures required.  
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**  
Do not spray on a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.

(Contd. on page 5)



**Trade name: 40786 Brushable Copperweld Weld Thru Primer**

(Contd. of page 4)

- Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/ Personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

### 123-86-4 n-butyl acetate

EL	Long-term value: 20 ppm
EV	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm

### 108-88-3 toluene

EL	Long-term value: 20 ppm R
EV	Long-term value: 20 ppm

### 7440-50-8 copper

EL	Long-term value: 1* 0.2** mg/m <sup>3</sup> *dusts and mists; **fume, as Cu
EV	Long-term value: 0.2* 1** mg/m <sup>3</sup> as copper, *fume; **dust and mists

### 1330-20-7 xylene

EL	Short-term value: 150 ppm Long-term value: 100 ppm
EV	Short-term value: 650 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm

### 12001-26-2 Mica

EL	Long-term value: 3 mg/m <sup>3</sup>
EV	Long-term value: 3(D) mg/m <sup>3</sup> respirable

### 100-41-4 ethylbenzene

EL	Long-term value: 20 ppm IARC 2B
EV	Short-term value: 540 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm

### 8052-41-3 Stoddard solvent

EL	Short-term value: 580 mg/m <sup>3</sup> Long-term value: 290 mg/m <sup>3</sup>
EV	Long-term value: 525 mg/m <sup>3</sup>

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.

(Contd. on page 6)



**Trade name: 40786 Brushable Copperweld Weld Thru Primer**

(Contd. of page 5)

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

<b>Form:</b>	Liquid
<b>Color:</b>	Copper colored
<b>Odor:</b>	Characteristic
<b>Odor threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	110 °C

· **Flash point:** 7 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 370 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

(Contd. on page 7)

# Safety Data Sheet

according to HPR, Schedule 1



Printing date 03/21/2018

Reviewed on 06/20/2017

Trade name: 40786 Brushable Copperweld Weld Thru Primer

(Contd. of page 6)

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower: 1.2 Vol %

Upper: 7.5 Vol %

· **Vapor pressure at 20 °C:** 29 hPa

· **Density at 20 °C:** 1.20549 g/cm<sup>3</sup>

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.

Kinematic: Not determined.

· **Solvent content:**

Organic solvents: 48.9 %

Water: 0.0 %

VOC content: 47.67 %

585.2 g/l / 4.88 lb/gal

Solids content: 49.5 %

· **Other information** No further relevant information available.

## 10 Stability and reactivity

· **Reactivity** No further relevant information available.

· **Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.

· **Conditions to avoid** No further relevant information available.

· **Incompatible materials:** No further relevant information available.

· **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral LD50 5,000 mg/kg (rat)

Dermal LD50 12,124 mg/kg (rabbit)

Inhalative LC50/4 h 5,320 mg/l (mouse)

(Contd. on page 8)

CA



**Trade name: 40786 Brushable Copperweld Weld Thru Primer**

(Contd. of page 7)

**1330-20-7 xylene**

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
	BENTONITE	suspected carcinogen <2% 14808-60-7

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)

# Safety Data Sheet

according to HPR, Schedule 1



Printing date 03/21/2018






Reviewed on 06/20/2017

Trade name: 40786 Brushable Copperweld Weld Thru Primer

(Contd. of page 8)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

· <b>UN-Number</b>	UN1263
· <b>DOT, TDG, IMDG, IATA</b>	
· <b>UN proper shipping name</b>	Paint
· <b>DOT</b>	1263 Paint, ENVIRONMENTALLY HAZARDOUS, special provision 640D
· <b>TDG</b>	PAINT (copper, 3-ethyl-2-methyl-2-(3-methylbutyl)-1,3-oxazolidine)
· <b>IMDG</b>	PAINT
· <b>IATA</b>	
· <b>Transport hazard class(es)</b>	
· <b>DOT</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>TDG, IMDG</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>IATA</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>Packing group</b>	II
· <b>DOT, TDG, IMDG, IATA</b>	
· <b>Environmental hazards:</b>	Product contains environmentally hazardous substances: zinc powder -zinc dust
· <b>Marine pollutant:</b>	Yes
· <b>Special marking (TDG):</b>	Symbol (fish and tree)
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>EMS Number:</b>	F-E, <u>S-E</u>

(Contd. on page 10)

CA



**Trade name: 40786 Brushable Copperweld Weld Thru Primer**

(Contd. of page 9)

· <b>Stowage Category</b>	<b>B</b>
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	<i>Not applicable.</i>
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· <b>Remarks</b>	Special marking with the symbol (fish and tree).
· <b>TDG</b>	
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II, ENVIRONMENTALLY HAZARDOUS

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

*None of the ingredient is listed.*

· **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
7440-50-8	copper
7440-66-6	zinc powder -zinc dust
1330-20-7	xylene
100-41-4	ethylbenzene
7429-90-5	aluminium
122-99-6	2-Phenoxyethanol
	COBALT CARBOXYLATE
104-68-7	Diethylene glycol monophenyl ether

· **TSCA (Toxic Substances Control Act):**

123-86-4	n-butyl acetate
108-88-3	toluene
7440-50-8	copper
7440-66-6	zinc powder -zinc dust
1330-20-7	xylene

(Contd. on page 11)



**Trade name: 40786 Brushable Copperweld Weld Thru Primer**

(Contd. of page 10)

100-41-4	ethylbenzene
143860-04-2	3-ethyl-2-methyl-2-(3-methylbutyl)-1,3-oxazolidine
90218-35-2	Dodecylbenzenesulfonic acid with 2-propanamine
67-64-1	acetone
79-20-9	methyl acetate
96-29-7	2-butanone oxime
67762-90-7	FUMED SILICA
64742-89-8	Solvent naphtha (petroleum), light aliph.
8052-41-3	Stoddard solvent
67701-03-5	FATTY ACID
25265-78-5	Tetrapropylene-benzene
110-12-3	5-methylhexan-2-one
110-73-6	2-ethylaminoethanol
7429-90-5	aluminium
122-99-6	2-Phenoxyethanol
15956-58-8	Manganese 2-Ethylhexanoate
149-57-5	2-ethylhexanoic acid
78-83-1	butanol
57-55-6	Methyl glycol
104-68-7	Diethylene glycol monophenyl ether
7732-18-5	water

· **Canadian substance listings:**

· **Canadian Domestic Substances List (DSL)**

123-86-4	n-butyl acetate
108-88-3	toluene
7440-50-8	copper
7440-66-6	zinc powder -zinc dust
1330-20-7	xylene
12001-26-2	Mica
100-41-4	ethylbenzene
90218-35-2	Dodecylbenzenesulfonic acid with 2-propanamine
67-64-1	acetone
79-20-9	methyl acetate
96-29-7	2-butanone oxime
67762-90-7	FUMED SILICA
64742-89-8	Solvent naphtha (petroleum), light aliph.
8052-41-3	Stoddard solvent
67701-03-5	FATTY ACID
110-12-3	5-methylhexan-2-one
110-73-6	2-ethylaminoethanol
7429-90-5	aluminium

(Contd. on page 12)

**Trade name: 40786 Brushable Copperweld Weld Thru Primer**

(Contd. of page 11)

122-99-6	2-Phenoxyethanol
15956-58-8	Manganese 2-Ethylhexanoate
149-57-5	2-ethylhexanoic acid
78-83-1	butanol
57-55-6	Methyl glycol
104-68-7	Diethylene glycol monophenyl ether
7732-18-5	water

· **Canadian Ingredient Disclosure list (limit 0.1%)**

100-41-4	ethylbenzene
----------	--------------

· **Canadian Ingredient Disclosure list (limit 1%)**

123-86-4	n-butyl acetate
108-88-3	toluene
7440-50-8	copper
12001-26-2	Mica

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02    GHS07    GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

toluene  
ethylbenzene  
Solvent naphtha (petroleum), light aliph.  
n-butyl acetate  
2-butanone oxime

· **Hazard statements**

H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.  
P242 Use non-sparking tools.  
P243 Take actions to prevent static discharges.

(Contd. on page 13)

# Safety Data Sheet

according to HPR, Schedule 1



Printing date 03/21/2018

Reviewed on 06/20/2017

**Trade name: 40786 Brushable Copperweld Weld Thru Primer**

(Contd. of page 12)

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
 P264 Wash thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P301+P310 If swallowed: Immediately call a poison center/doctor.  
 P321 Specific treatment (see on this label).  
 P331 Do NOT induce vomiting.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308+P313 IF exposed or concerned: Get medical advice/attention.  
 P312 Call a poison center/doctor if you feel unwell.  
 P314 Get medical advice/attention if you feel unwell.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P337+P313 If eye irritation persists: Get medical advice/attention.  
 P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Rita Joiner (rjoiner@semproducts.com)

· **Date of preparation / last revision** 03/21/2018 / 15

· **Abbreviations and acronyms:**

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 14)

**Safety Data Sheet**  
according to HPR, Schedule 1



Printing date 03/21/2018

Reviewed on 06/20/2017

**Trade name: 40786 Brushable Copperweld Weld Thru Primer**

PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative

(Contd. of page 13)

· **\* Data compared to the previous version altered.**

CA