1 Identification

- · Product identifier
- · Trade name: 40977 Sound & Seal
- · Article number: 40977
- · Application of the substance / the mixture Sealant
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: SEM Products Inc. 1685 Overview Drive

Rock Hill, SC 29730 803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corrosion - Category 1B H314 Causes severe skin burns and eye damage.

Serious Eye Damage - Category 1 H318 Causes serious eye damage.



Acute Toxicity (Oral) - Category 4 H302 Harmful if swallowed.

Skin Sensitizer - Category 1 H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure - H335 May cause respiratory irritation.

Category 3

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

CASTOR OIL GLYCIDAL ETHER

2,4,6-tris(dimethylaminomethyl)phenol

EPOXY RESIN MODIFIER

bisphenolA(chloro)oxirane polymer

N-(*3-*(*trimethoxysilyl*)*propyl*)*ethylenediamine*

(Contd. on page 2)

SEM

Printing date 03/21/2018 Reviewed on 06/21/2017

Trade name: 40977 Sound & Seal

(Contd. of page 1)

· Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 If swallowed: Call a poison center/doctor if you feel unwell. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor. P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH 2
FIRE 1

Health = 2Fire = 1

REACTIVITY 0 Reactivity = 0

3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous	components:	
	EPOXY RESIN MODIFIER	10-30% w/w
74398-71-3	CASTOR OIL GLYCIDAL ETHER	10-30% w/w
		(Contd. on page 3)

Ć۸ -

Trade name: 40977 Sound & Seal

		(Contd. of page 2)
	bisphenolA(chloro)oxirane polymer	≥5-<10% w/w
67762-90-7	FUMED SILICA	3-7% w/w
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	≥1-<5% w/w
919-30-2	3-aminopropyltriethoxysilane	≥1-<1.5% w/w
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	0.5-1.5% w/w
	EPOXY RESIN	0.5-1.5% w/w
1760-24-3	N-(3-(trimethoxysilyl)propyl)ethylenediamine	≥0.1-<1% w/w

4 First aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)

-CA

Trade name: 40977 Sound & Seal

(Contd. of page 3)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



Trade name: 40977 Sound & Seal

(Contd. of page 4)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Physical and chemical proper	ties — — — — — — — — — — — — — — — — — — —
Information on basic physical and o	chemical properties
General Information	• •
Appearance:	
Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	261 °C
Flash point:	111 °C
Flammability (solid, gaseous):	Not applicable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure:	Not determined.
Density at 20 °C:	1.15387 g/cm³
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.

(Contd. on page 6)



Trade name: 40977 Sound & Seal

	(Contd. of page
· Solvent content: Organic solvents: VOC content:	0.0 % 0.02 %
Solids content: · Other information	99.7 % No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (Inte	rnational Agency for Research on Cancer)	
13463-67-7	titanium dioxide	28
1333-86-4	Carbon black	28
106-89-8	1-chloro-2,3-epoxypropane	2A
64-17-5	ethanol	1
· NTP (Natio	onal Toxicology Program)	
106-89-8 1	-chloro-2,3-epoxypropane	R

(Contd. on page 7)



Trade name: 40977 Sound & Seal

(Contd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.

1 4 0	7		C	
4	rangnar	am	orma	tion

TTAT	3 7 1
I / /N/_	Number

· DOT, TDG, IMDG, IATA UN1760

· UN proper shipping name

• **DOT** Corrosive liquids, n.o.s. (3-aminopropyltriethoxysilane)

• TDG 1760 Corrosive liquids, n.o.s. (3-aminopropyltriethoxysilane)

· IMDG, IATA CORROSIVE LIQUID, N.O.S. (3-aminopropyltriethoxysilane)

- · Transport hazard class(es)
- $\cdot DOT$



Class 8 *Corrosive substances*

(Contd. on page 8)

ĆA

Trade name: 40977 Sound & Seal

	(Contd. of pag
Label	8
TDG, IMDG, IATA	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
Class	8 Corrosive substances
Label	8
Packing group	
DOT, TDG, IMDG, IATA	III
Environmental hazards:	
Environmeniai nazaras: Marine pollutant:	No
Special precautions for user	Warning: Corrosive substances
EMS Number:	F- A , S - B
Stowage Category	A CHARLES CHARLES
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
-	
DOT Quantity limitations	On passenger aircraft/rail: 5 L
Quantity timuations	On cargo aircraft only: 60 L
Remarks	ORM-D 49CFR 173-150,156,306
	0.1 2 170111110 100,100,000
TDG	C-1 F1
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
	Maximum nei quantity per outer packaging. 1000 mi
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1760 CORROSIVE LIQUIDS, N.O.S. (
-	AMINOPROPYLTRIETHOXYSILANE), 8, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

Sura	
· Section 3:	55 (extremely hazardous substances):
107-15-3	ethylenediamine
106-89-8	1-chloro-2,3-epoxypropane

· Section 313 (Specific toxic chemical listings):

107-21-1 ethanediol

(Contd. on page 9)

Trade name: 40977 Sound & Seal

67-56-1	methanol (Contd. of pa
	1-chloro-2,3-epoxypropane
	exic Substances Control Act):
,	3 CASTOR OIL GLYCIDAL ETHER
	6 bisphenolA(chloro)oxirane polymer
	7 FUMED SILICA
90-72-	2 2,4,6-tris(dimethylaminomethyl)phenol
	2 3-aminopropyltriethoxysilane
	8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane
	7 titanium dioxide
1760-24-	3 N-(3-(trimethoxysilyl)propyl)ethylenediamine
107-21-	-I ethanediol
1333-86-	4 Carbon black
67-56-	· I methanol
107-15-	3 ethylenediamine
106-89-	8 1-chloro-2,3-epoxypropane
64-17-	5 ethanol
Canadian	substance listings:
Canadian	Domestic Substances List (DSL)
74398-71-	3 CASTOR OIL GLYCIDAL ETHER
	6 bisphenolA(chloro)oxirane polymer
67762-90-	7 FUMED SILICA
90-72-	2 2,4,6-tris(dimethylaminomethyl)phenol
	2 3-aminopropyltriethoxysilane
	8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane
	7 titanium dioxide
	3 N-(3-(trimethoxysilyl)propyl)ethylenediamine
	-1 ethanediol
	4 Carbon black
	1 methanol
	3 ethylenediamine
64-17-	5 ethanol
	Ingredient Disclosure list (limit 0.1%)
None of th	ne ingredients is listed.
	Ingredient Disclosure list (limit 1%)
None of th	ne ingredients is listed.

(Contd. of page 9)

Printing date 03/21/2018 Reviewed on 06/21/2017

Trade name: 40977 Sound & Seal

· Hazard pictograms





· Signal word Danger

· Hazard-determining components of labeling:

CASTOR OIL GLYCIDAL ETHER 2,4,6-tris(dimethylaminomethyl)phenol

EPOXY RESIN MODIFIER

bisphenolA(chloro)oxirane polymer

N-(*3-*(*trimethoxysilyl*)*propyl*)*ethylenediamine*

· Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 If swallowed: Call a poison center/doctor if you feel unwell. *P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.*

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor. P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. P333+P313

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner (rjoiner@semproducts.com)
- · Date of preparation / last revision 03/21/2018 / 6

(Contd. on page 11)



Trade name: 40977 Sound & Seal

(Contd. of page 10)

· Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

* Data compared to the previous version altered.

CA.