

Printing date 03/14/2018 Reviewed on 06/28/2017

1 Identification

- · Product identifier
- · Trade name: 41033 Euro Trim Black Gloss Aerosol
- · Article number: 41033
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive

Rock Hill, SC 29730

803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture





GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

 (Contd. on page 2)

-USA



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 41033 Euro Trim Black - Gloss Aerosol

(Contd. of page 1)

· Hazard pictograms









GHS04

GHS07

· Signal word Danger

· Hazard-determining components of labeling:

acetone

toluene

butanone

P501

n-butyl acetate

· Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

regulations.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

1 recumionary sta	ichtents
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	If on skin: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P33	8 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a poison center/doctor if you feel unwell.
P321	Specific treatment (see on this label).
P314	Get medical advice/attention if you feel unwell.
P362+P364	Take off contaminated clothing and wash it before reuse.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international

(Contd. on page 3)

SEM

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 41033 Euro Trim Black - Gloss Aerosol

(Contd. of page 2)

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 4 Reactivity = 3

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

68476-86-8 Petroleum gases, liquefied, sweetened 13- 110-19-0 isobutyl acetate 13- 1330-20-7 xylene ≥7- 108-88-3 toluene 5- 78-93-3 butanone 5-	
110-19-0 isobutyl acetate 13- 1330-20-7 xylene ≥7- 108-88-3 toluene 5- 78-93-3 butanone 5-	13-30%
1330-20-7 xylene ≥7- 108-88-3 toluene 5- 78-93-3 butanone 5-	13-30%
108-88-3 toluene 5- 78-93-3 butanone 5-	13-30%
78-93-3 butanone 5-	?7-<10%
	5-7%
123 86 4 n hytril gostate	5-7%
1.5	1.5-5%
V VI I	1.5-5%
1333-86-4 Carbon black 1-1	1-1.5%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 41033 Euro Trim Black - Gloss Aerosol

(Contd. of page 3)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

67-64-1 acetone	200 ppm
110-19-0 isobutyl acetate	450 ppm
1330-20-7 xylene	130 ppm
108-88-3 toluene	67 ppm
78-93-3 butanone	200 ppm
123-86-4 n-butyl acetate	5 ppm
763-69-9 ethyl 3-ethoxypropionate	1.6 ppm
1333-86-4 Carbon black	9 mg/m³
108-65-6 2-methoxy-1-methylethyl acetate	50 ppm
112926-00-8 precipitated Silica (Silica-Amorphous)	18 mg/m
95-63-6 1,2,4-trimethylbenzene	140 ppm
100-41-4 ethylbenzene	33 ppm
PAC-2:	
67-64-1 acetone	3200* ppr
110-19-0 isobutyl acetate	1300* ppr
1330-20-7 xylene	
108-88-3 toluene	
78-93-3 butanone	2700* ppr
123-86-4 n-butyl acetate	200 ppm

USA



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 41033 Euro Trim Black - Gloss Aerosol

7(2,(0,0),1,12,1,1	(Contd. of page
763-69-9 ethyl 3-ethoxypropionate	18 ppm
1333-86-4 Carbon black	99 mg/m^3
108-65-6 2-methoxy-1-methylethyl acetate	1,000 ppm
112926-00-8 precipitated Silica (Silica-Amorphous)	200 mg/m ³
95-63-6 1,2,4-trimethylbenzene	360 ppm
100-41-4 ethylbenzene	1100* ppn
· PAC-3:	
67-64-1 acetone	5700* ppm
110-19-0 isobutyl acetate	7500** ppn
1330-20-7 xylene	2500* ppm
108-88-3 toluene	3700* ppm
78-93-3 butanone	4000* ppm
123-86-4 n-butyl acetate	3000* ppm
763-69-9 ethyl 3-ethoxypropionate	110 ppm
1333-86-4 Carbon black	590 mg/m^3
108-65-6 2-methoxy-1-methylethyl acetate	5000* ppm
112926-00-8 precipitated Silica (Silica-Amorphous)	1,200 mg/m
95-63-6 1,2,4-trimethylbenzene	480 ppm
100-41-4 ethylbenzene	1800* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special measures required.
- $\cdot \textit{Information about protection against explosions and fires:}$

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

(Contd. on page 6)

SEM

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 41033 Euro Trim Black - Gloss Aerosol

At this	s time, the other constituents have no known exposure limits.	(Contd. of p
67-64-	-1 acetone	
PEL 1	Long-term value: 2400 mg/m³, 1000 ppm	
REL I	Long-term value: 590 mg/m³, 250 ppm	
TLV S	Short-term value: 1187 mg/m³, 500 ppm	
	Long-term value: 594 mg/m³, 250 ppm BEI	
	9-0 isobutyl acetate	
	Long-term value: 700 mg/m³, 150 ppm	
	Long-term value: 700 mg/m³, 150 ppm	
	Short-term value: 712 mg/m³, 150 ppm	
	Long-term value: 238 mg/m³, 50 ppm	
	20-7 xylene	
PEL 1	Long-term value: 435 mg/m³, 100 ppm	
	Short-term value: 655 mg/m³, 150 ppm	
1	Long-term value: 435 mg/m³, 100 ppm	
	Short-term value: 651 mg/m³, 150 ppm	
	Long-term value: 434 mg/m³, 100 ppm BEI	
108-88	8-3 toluene	
	Long-term value: 200 ppm	
	Ceiling limit value: 300; 500* ppm	
	*10-min peak per 8-hr shift	
	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm	
	Long-term value: 75 mg/m³, 20 ppm BEI	
78-93-	2-3 butanone	
PEL 1	Long-term value: 590 mg/m³, 200 ppm	
REL S	Short-term value: 885 mg/m³, 300 ppm	
1	Long-term value: 590 mg/m³, 200 ppm	
	Short-term value: 885 mg/m³, 300 ppm	
	Long-term value: 590 mg/m³, 200 ppm BEI	
	6-4 n-butyl acetate	
	Long-term value: 710 mg/m³, 150 ppm	
	Long-term value: 950 mg/m³, 200 ppm	
	Short-term value: 712 mg/m³, 150 ppm	
	Long-term value: 238 mg/m³, 50 ppm	
1333-8	86-4 Carbon black	
PEL 1	Long-term value: 3.5 mg/m³	
REL I	Long-term value: 3.5* mg/m³ *0.1 in presence of PAHs;See Pocket Guide Apps.A+C	
TLV	Long-term value: 3* mg/m³	
	*inhalable fraction	



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 41033 Euro Trim Black - Gloss Aerosol

(Contd. of page 6)

· Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

1330-20-7 xylene

BEI 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

108-88-3 toluene

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

78-93-3 butanone

BEI 2 mg/L

Medium: urine Time: end of shift Parameter: MEK

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately. Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 8)

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 41033 Euro Trim Black - Gloss Aerosol

(Contd. of page 7)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses



Tightly sealed goggles

O TOT			
9 Physical	and	chomical	nranarties
J I II you u	unu	Chemicai	properties

T C	7 .	7 . 1			
· Information	on hasic	nhveical	and c	homical	nranerfies
III OI III WIIOII	on busic	preysteut	unu ci	<i>iciiiicai</i>	properties

· General Information

· Appearance:

Form: Aerosol

Color: According to product specification

· Odor: Characteristic · Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: 55.8-56.6 °C

· Flash point: -103 °C

· Flammability (solid, gaseous): Not applicable.

405 °C · Ignition temperature:

Not determined. · Decomposition temperature:

· Auto igniting: Product is not selfigniting.

· Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

1.9 Vol % Lower: 13 Vol % Upper:

· Vapor pressure at 20 °C: 233 hPa

· Density at 20 °C: 0.75135 g/cm³

(Contd. on page 9)



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 41033 Euro Trim Black - Gloss Aerosol

		(Contd. of page
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octan	ol/water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	91.0 %	
VOC content:	65.03 %	
	649.1 g/l / 5.42 lb/gl	
Solids content:	8.9 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- $\cdot \textit{Possibility of hazardous reactions} \ \textit{No dangerous reactions known}.$
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 1	· LD/LC50 values that are relevant for classification:				
1330-20-7	1330-20-7 xylene				
Oral	LD50	4,300 mg/kg (rat)			
Dermal	<i>LD50</i>	LD50 2,000 mg/kg (rabbit)			
108-88-3 to	108-88-3 toluene				
Oral	LD50	5,000 mg/kg (rat)			
Dermal	<i>LD50</i>	12,124 mg/kg (rabbit)			
Inhalative	Inhalative LC50/4 h 5,320 mg/l (mouse)				

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 10)

-USA



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 41033 Euro Trim Black - Gloss Aerosol

(Contd. of page 9)

Irritant

· Carcinogenic categories

· IARC (Inte	· IARC (International Agency for Research on Cancer)		
1330-20-7	xylene	3	
108-88-3	toluene	3	
1333-86-4	Carbon black	2B	
100-41-4	ethylbenzene	2B	
3.77773 (3.7)			

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

68911-87-5 montmorilontie clay complex

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

TONE	nort in	torma	1707
	port in		
 L COLUD	010 010	10111100	

٠	UN-N	umber
---	------	-------

· DOT, ADR, IMDG, IATA UN1950

· UN proper shipping name

DOT Aerosols, flammable
ADR 1950 Aerosols
IMDG AEROSOLS

(Contd. on page 11)

SEM

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 41033 Euro Trim Black - Gloss Aerosol

IATA	AEROSOLS, flammable
Transport hazard class(es)	
DOT	
Class	2.1
Label	2.1 2.1
	2.1
ADR	
Class	2 5F Gases
Label	2.1
IMDG, IATA	
2	
Class	2.1
Label	2.1
Packing group	
DOT, ADR, IMDG, IATA	Void
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Gases
EMS Number: Stowage Code	F-D,S-U SW1 Protected from sources of heat.
Stowage Code	SW22 For AEROSOLS with a maximum capacity of 1 litro
	Category A. For AEROSOLS with a capacity above 1 litre
	Category B. For WASTE AEROSOLS: Category C, Clear of living
Segregation Code	quarters. SG69 For AEROSOLS with a maximum capacity of 1 litro
Segregation Code	Segregation as for class 9. Stow "separated from" class 1 except for
	division 1.4. For AEROSOLS with a capacity above 1 litre
	Segregation as for the appropriate subdivision of class 2. For
	WASTE AEROSOLS: Segregation as for the appropriate subdivisio of class 2.
Towns and in Last, we say I am a few A	·
Transport in bulk according to Annex	t II OJ

(Contd. on page 12)

SEM

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 41033 Euro Trim Black - Gloss Aerosol

		(Contd. of page 11
· Transport/Additional information:		
\cdot DOT		
· Quantity limitations	On passenger aircraft/rail: 75 kg	
	On cargo aircraft only: 150 kg	
\cdot ADR		
· Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
· IMDG		
· Limited quantities (LQ)	1L	
\cdot Excepted quantities (\widetilde{EQ})	Code: E0	
	Not permitted as Excepted Quantity	
· UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

None of the	e ingredient is listed.	
Section 31.	3 (Specific toxic chemical listings):	
1330-20-7	xylene	
	Acrylic Resin	
108-88-3	toluene	
78-93-3	butanone	
95-63-6	1,2,4-trimethylbenzene	
100-41-4	ethylbenzene	
TSCA (Tox	xic Substances Control Act):	
67-64-	1 acetone	
110-19-0	o isobutyl acetate	
1330-20-7	7 xylene	
108-88-3	3 toluene	
78-93-3	3 butanone	
123-86-4	4 n-butyl acetate	
763-69-9	9 ethyl 3-ethoxypropionate	
1333-86-4	4 Carbon black	
108-65-6	5 2-methoxy-1-methylethyl acetate	
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate	
68911-87-3	5 montmorilontie clay complex	
64742-82-	Naphtha (petroleum), hydrodesulfurized heavy	
95-63-6	1,2,4-trimethylbenzene	
100-41-4	4 ethylbenzene	

USA



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 41033 Euro Trim Black - Gloss Aerosol

(Contd. of page 12) · TSCA new (21st Century Act) (Substances not listed) 68476-86-8 Petroleum gases, liquefied, sweetened · Proposition 65 · Chemicals known to cause cancer: 1330-20-7 xylene 1333-86-4 Carbon black 95-63-6 1,2,4-trimethylbenzene 100-41-4 ethylbenzene · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: 108-88-3 toluene · Cancerogenity categories · EPA (Environmental Protection Agency) 67-64-1 acetone 1330-20-7 xylene 108-88-3 toluene II78-93-3 butanone 95-63-6 1,2,4-trimethylbenzene II 100-41-4 ethylbenzene D· TLV (Threshold Limit Value established by ACGIH) 67-64-1 acetone *A4* 1330-20-7 xylene *A4* 108-88-3 toluene A41333-86-4 Carbon black A4100-41-4 ethylbenzene *A3* · NIOSH-Ca (National Institute for Occupational Safety and Health)

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms

1333-86-4 Carbon black









GHS02 GHS04

- · Signal word Danger
- · Hazard-determining components of labeling:

acetone toluene butanone n-butyl acetate

(Contd. on page 14)



Trade name: 41033 Euro Trim Black - Gloss Aerosol

(Contd. of page 13)

· Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	If on skin: Wash with plenty of water.
P301 + P310	IF INHALED. Remove person to fresh air and keen comfortable for breath

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner (rjoiner@semproducts.com)
- · Date of preparation / last revision 03/14/2018 / 10
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

(Contd. on page 15)

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 41033 Euro Trim Black - Gloss Aerosol

(Contd. of page 14)

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flam. Aerosol 1: Aerosols - Category 1 Press. Gas: Gases under pressure - Compressed gas

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

* Data compared to the previous version altered.