SEM

Printing date 03/21/2018 Reviewed on 06/20/2017

1 Identification

- · Product identifier
- · Trade name: SR201-SR204 Medium Reducer
- · Article number: SR201, SR204
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc.

1685 Overview Drive

Rock Hill, SC 29730

803 207 8225

· Information department:

cust\_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

## 2 Hazard identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids - Category 3

H226 Flammable liquid and vapour.



GHS08 Health hazard

Carcinogenicity – Category 2

H351 Suspected of causing cancer.



GHS07

Acute Toxicity (Inhalation) - Category 4

H332 Harmful if inhaled.

Specific Target Organ Toxicity - Single Exposure -

H336 May cause drowsiness or dizziness.

Category 3

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

- · Signal word Warning
- · Hazard-determining components of labeling:

Solvent naphtha (petroleum), light arom.

n-butyl acetate

1,2,4-trimethylbenzene

(Contd. on page 2)

Trade name: SR201-SR204 Medium Reducer

(Contd. of page 1)

1-methoxy-2-propanol

### · Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H351 Suspected of causing cancer.

H336 May cause drowsiness or dizziness.

### · Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

smoking.

P240 *Ground and bond container and receiving equipment.* 

P241 *Use explosion-proof [electrical/ventilating/lighting] equipment.* 

P242 *Use non-sparking tools.* 

P243 Take actions to prevent static discharges.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P370+P378 *In case of fire: Use for extinction: CO2, powder or water spray.* Store in a well-ventilated place. Keep container tightly closed. P403+P233

Store in a well-ventilated place. Keep cool. P403+P235

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1Fire = 3REACTIVITY 0 Reactivity = 0

## 3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:

123-86-4 n-butyl acetate 15-40% w/w

(Contd. on page 3)

Reviewed on 06/20/2017

Trade name: SR201-SR204 Medium Reducer

		(Contd. of page 2)
	2-methoxy-1-methylethyl acetate	15-40% w/w
	1-methoxy-2-propanol	10-30% w/w
	Solvent naphtha (petroleum), light arom.	3-7% w/w
	4-hydroxy-4-methylpentan-2-one	1-5% w/w
	1,2,4-trimethylbenzene	1-5% w/w
	mesitylene	≥0.1-≤1% w/w
98-82-8	cumene	<i>≥</i> 0.1- <i>≤</i> 1% w/w

### 4 First aid measures

Printing date 03/21/2018

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Trade name: SR201-SR204 Medium Reducer

See Section 13 for disposal information.

(Contd. of page 3)

## 7 Handling and storage

- · Handling:
- Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/Personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

### 123-86-4 n-butyl acetate

- EL Long-term value: 20 ppm
- EV Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm

### 108-65-6 2-methoxy-1-methylethyl acetate

- EL Short-term value: 75 ppm
  - Long-term value: 50 ppm
- EV Long-term value: 270 mg/m<sup>3</sup>, 50 ppm

### 107-98-2 1-methoxy-2-propanol

- EL Short-term value: 75 ppm
  - Long-term value: 50 ppm
- EV Short-term value: 550 mg/m³, 150 ppm Long-term value: 365 mg/m³, 100 ppm

## 123-42-2 4-hydroxy-4-methylpentan-2-one

- EL Long-term value: 50 ppm
- EV Short-term value: 360 mg/m³, 75 ppm Long-term value: 240 mg/m³, 50 ppm

### 98-82-8 cumene

- EL Short-term value: 75 ppm Long-term value: 25 ppm
  - IARC 2B

(Contd. on page 5)



Trade name: SR201-SR204 Medium Reducer

(Contd. of page 4)

EV Long-term value: 245 mg/m³, 50 ppm Skin

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

# 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

*Color:* According to product specification

Odor: CharacteristicOdor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

*Melting point/Melting range:* Undetermined.

Boiling point/Boiling range: 82 °C

• Flash point: 27 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 270 °C

· Decomposition temperature: Not determined.

(Contd. on page 6)

Trade name: SR201-SR204 Medium Reducer

	(Contd. of page
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	20 Vol %
· Vapor pressure at 20 °C:	12 hPa
· Density at 20 °C:	$0.916 \ g/cm^3$
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wa	tter): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	100.0 %
VOC content:	100.00 %
	916.0 g/l / 7.64 lb/gl
Solids content:	0.0 %
· Other information	No further relevant information available.

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:		
64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6,800 mg/kg (rat)
Dermal	<i>LD50</i>	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	> 10.2  mg/L (rat)

(Contd. on page 7)

Trade name: SR201-SR204 Medium Reducer

 (Contd. of page 6)

 95-63-6 1,2,4-trimethylbenzene

 Oral
 LD50
 5,000 mg/kg (rat)

· Primary irritant effect:

- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
1330-20-7 xylene		3
98-82-8 cumer	?	2B
· NTP (National Toxicology Program)		
98-82-8 cumene		R

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

## 14 Transport information

- · UN-Number
- · DOT, TDG, IMDG, IATA UN1263

(Contd. on page 8)

according to HPR, Schedule 1

Printing date 03/21/2018 Reviewed on 06/20/2017

Trade name: SR201-SR204 Medium Reducer

(Contd. of page 7) · UN proper shipping name  $\cdot DOT$ Paint  $\cdot TDG$ 1263 Paint · IMDG, IATA **PAINT** · Transport hazard class(es)  $\cdot DOT$ · Class 3 Flammable liquids · Label 3 · TDG, IMDG, IATA 3 Flammable liquids · Class · Label 3 · Packing group · DOT, TDG, IMDG, IATA III · Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Flammable liquids · EMS Number: F-E,S-E· Stowage Category · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: On passenger aircraft/rail: 60 L · Quantity limitations On cargo aircraft only: 220 L · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · IMDG · Limited quantities (LQ) 5L· Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · UN ''Model Regulation'': UN 1263 PAINT, 3, III

Trade name: SR201-SR204 Medium Reducer

(Contd. of page 8)

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

95-63-6	1,2,4-trimethylbenzene
1330-20-7	xylene

· TSCA (Toxic Substances Control Act):

123-86-4	n-butyl acetate
108 65 6	2 mathory 1 mathylathyl ac

108-65-6 | 2-methoxy-1-methylethyl acetate 107-98-2 | 1-methoxy-2-propanol

123-42-2 4-hydroxy-4-methylpentan-2-one

95-63-6 1,2,4-trimethylbenzene

108-67-8 mesitylene

98-82-8 cumene

1330-20-7 xylene

98-82-8 cumene

### · Canadian substance listings:

	· Canadian Domestic Substances List (DSL)		
	123-86-4 n-butyl acetate		
108-65-6	2-methoxy-1-methylethyl acetate		
	1-methoxy-2-propanol		
	123-42-2 4-hydroxy-4-methylpentan-2-one		
	1,2,4-trimethylbenzene		
108-67-8	67-8 mesitylene		
1330-20-7	1330-20-7 xylene		
98-82-8	cumene		

### · Canadian Ingredient Disclosure list (limit 0.1%)

95-63-6 1,2,4-trimethylbenzene

108-67-8 mesitylene

## · Canadian Ingredient Disclosure list (limit 1%)

123-86-4 n-butyl acetate

107-98-2 1-methoxy-2-propanol

123-42-2 4-hydroxy-4-methylpentan-2-one

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02 GHS07

GHS08

(Contd. on page 10)

Trade name: SR201-SR204 Medium Reducer

(Contd. of page 9)

### · Signal word Warning

### · Hazard-determining components of labeling:

Solvent naphtha (petroleum), light arom.

*n-butyl* acetate

1,2,4-trimethylbenzene

1-methoxy-2-propanol

### · Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H351 Suspected of causing cancer.

H336 May cause drowsiness or dizziness.

#### · Precautionary statements

	P201	Obtain special instructions before use.
--	------	---

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

*P240 Ground and bond container and receiving equipment.* 

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P242 Use non-sparking tools.

*P243 Take actions to prevent static discharges.* 

P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

*P308+P313 IF exposed or concerned: Get medical advice/attention.* 

P312 Call a poison center/doctor if you feel unwell.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner (rjoiner@semproducts.com)
- · Date of preparation / last revision 03/21/2018 / 6
- · Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

(Contd. on page 11)

Trade name: SR201-SR204 Medium Reducer

(Contd. of page 10)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

· \* Data compared to the previous version altered.