SEM 2K LOWER PANEL PROTECTION STANDARD OPERATING PROCEDURE



Clean with SEM Solve or XXX Universal Surface **Cleaner**. Wipe clean in one direction with dry. lint-free cloth.

PRODUCT LIST





SAND, CLEAN & PRIME

IDENTIFY TEXTURE



Sand with 180-220 grit sandpaper.

Prime any bare metal and aluminum areas as per manufacturer's instructions.

Sand e-coat with a Maroon Scuff Pad.

Sand primer with 180-220 grit sandpaper.

Blow off and tack clean before application.

Use the photo on the back of box to choose the appropriate texture.

Scan the QR code to download the product TDS for detailed instructions on how to duplicate the texture

PREP

Part	Product	Size
38371	SEM Solve	Gallon
38373	SEM Solve	20 oz. Aerosol
38374	SEM Solve	Square Quart
77771	XXX Universal Surface Cleaner	Gallon
77774	XXX Universal Surface Cleaner	Quart



SAND. CLEAN & PRIME

Part	Product	Size
SA6180	6" Grip Multi-hole 180-grit	6" DA
SA6220	6" Grip Multi-hole 220-grit	6" DA
SA4947	4.5" x 9" Maroon Scuff Pad	4.5" x 9"



Add activator to bottle of **2K Urethane Chip Guard**. Shake bottle for two minutes before applying.

2K Urethane Chip Guard can also be tinted with solvent-based toners by adding 1 oz. of tint to the bottle.

Tinting is not required



MIX	
Dowl	

Part	Product	Size
52000	2K Urethane Chip Guard	Kit



Attach mixed bottle to 2K Urethane Chip Guard Applicator or pour into spray gun called out in instructions for duplicating texture.

Follow instructions for correct air pressure and distance.

(i)



Remove masking tape while final coat is still wet. Clean gun with XXX Universal Gun Cleaner or solvent complaint with VOC regulations in your area.

Visit our website for more information:

www.semproducts.com



APPLY, FINISH & CLEAN

110000	Size
2K Urethane Chip Guard Applicator	Each
XXX Universal Gun Cleaner	20 oz. Aeroso

SEM Products

Rock Hill, SC 29730 Tech Support: 1-800-831-1122 Customer Care: 1-866-327-7829 semproducts.com