



# INNER PANEL CORROSION PROTECTION

## STANDARD OPERATING PROCEDURE

# 1

## THE Rigid 360° Applicator



**Rust Preventer Cavity Wax** is easily applied with a 360° spray pattern when using the **Rigid 360° Applicator**.

⚠ Do not spray without tip being inserted into inner panel access point.

# 2

## PREP & APPLY



Clean accessible surfaces with **SEM Solve** or **XXX Universal Surface Cleaner**.

Remove cap from **Rust Preventer Cavity Wax** and attach straw or **Rigid 360° Applicator**.  
Apply 1-2 coats

ⓘ Change angle and depth of the tip inside panel to ensure coverage.

## Pro Tip



Mark the end of the **Rigid 360° Applicator** with masking tape to keep from spraying outside the panel.

# 3

## CLEAN APPLICATOR



Clean **Rigid 360° Applicator** by attaching the tip and Applicator to **XXX Universal Gun Cleaner**.

ⓘ Spray into enclosed container or clean cloth until applicator is clean. Wipe off residual remnants from outside of tube

## PRODUCT LIST



## PREP

Part	Product	Size
38371	SEM Solve	Gallon
38373	SEM Solve	20 oz. Aerosol
38374	SEM Solve	Square Quart
77771	XXX Universal Surface Cleaner	Gallon
77774	XXX Universal Surface Cleaner	Quart



## APPLICATIONS

Part	Product	Size
39573	Rust Preventer Cavity Wax	24 oz. Aerosol



## EQUIPMENT

Part	Product	Size
71360	Rigid 360° Applicator	Kit



## CLEAN-UP

Part	Product	Size
77743	XXX Gun Cleaner	20 oz. Aerosol
77763	XXX Universal Gun Cleaner	

## SEM Products

Rock Hill, SC 29730  
Tech Support: 1-800-831-1122  
Customer Care: 1-866-327-7829  
[semproducts.com](http://semproducts.com)

LEARN MORE ABOUT RUST PREVENTER CAVITY WAX AT  
[semproducts.com/product/rust-preventer-cavity-wax](http://semproducts.com/product/rust-preventer-cavity-wax)