

PROTECTIVE COATING SYSTEM



TREAT, RESTORE AND PROTECT

SAVE TIME

FEWER STEPS & FASTER APPLICATION

SAVE MONEY

NO METAL CONDITIONER NEEDED

LESS WASTE

PACKAGING ALLOWS MULTIPLE USES



**APPLY DIRECTLY TO RUST AND BARE SANDED STEEL
DRIES TO A ROCK HARD NON-POROUS SURFACE**


RESTORATION



EQUIPMENT



INDUSTRIAL



HOME & GARDEN



A high gloss, moisture cured, urethane coating for restoring and protecting rusty metal.

- Paint direct to rust or bare sanded steel
- Will not chip, crack or peel
- Seals current rust and prevents new rust formation
- Fast coverage
- Dries to a glossy, non-porous, rock hard surface
- Topcoat for UV resistance
- Excellent durability and chemical resistance
- Apply by brush or spray gun

RUST TRAP BLACK

45501	Gallon
45504	Quart
45508	Pint

RUST TRAP SILVER

45514	Quart
45518	Pint

RUST TRAP FLATTENER

45594	Quart
45598	Pint



BEFORE



AFTER



1



Clean thoroughly with **38373 SEM Solve** to remove grease and oil. Wipe dry in one direction to avoid smearing.

2



Remove loose rust scale by sanding, grinding or using a wire brush. Removing additional rust will result in a better final appearance.

Abrade other surfaces with 180 grit sandpaper.

Blow off and re-clean with **SEM Solve**. Repeat until surface is free of contaminants.

3




Stir or gently shake **Rust Trap**.

Pour amount to be used into mixing cup or another container. Do not return unused material back into can.

Wipe pour spout and inside of cap prior to recapping.

4



Apply 2 medium coats with a brush or spray gun allowing 5 – 15 minutes flash time between coats. Apply a second coat while first coat is still wet. First coat should not achieve full coverage and second coat should be applied in the same manner.

Allow final coat to cure for 8 – 24 hours before returning part to service.



SEM Products, Inc.
 Rock Hill, SC 29730
 1-800-831-1122
semproducts.com



Learn more about Rust Trap
semproducts.com/rust-trap