



INNER PANEL CORROSION PROTECTION

STANDARD OPERATING PROCEDURE

1

THE Rigid 360° Applicator



Rust Preventer Cavity Wax is easily applied with a 360° spray pattern when using the **Rigid 360° Applicator**.

⚠ Do not spray without tip being inserted into inner panel access point.

2

PREP & APPLY



Clean accessible surfaces with **SEM Solve** or **XXX Universal Surface Cleaner**.

Remove cap from **Rust Preventer Cavity Wax** and attach straw or **Rigid 360° Applicator**.
Apply 1-2 coats

ⓘ Change angle and depth of the tip inside panel to ensure coverage.

Pro Tip



Mark the end of the **Rigid 360° Applicator** with masking tape to keep from spraying outside the panel.

3

CLEAN APPLICATOR



Clean **Rigid 360° Applicator** by attaching the tip and Applicator to **XXX Universal Gun Cleaner**.

ⓘ Spray into enclosed container or clean cloth until applicator is clean. Wipe off residual remnants from outside of tube

PRODUCT LIST



PREP

Part	Product	Size
38371	SEM Solve	Gallon
38373	SEM Solve	20 oz. Aerosol
38374	SEM Solve	Square Quart
77771	XXX Universal Surface Cleaner	Gallon
77774	XXX Universal Surface Cleaner	Quart



APPLICATIONS

Part	Product	Size
39573	Rust Preventer Cavity Wax	24 oz. Aerosol



EQUIPMENT

Part	Product	Size
71360	Rigid 360° Applicator	Kit



CLEAN-UP

Part	Product	Size
77743	XXX Gun Cleaner	20 oz. Aerosol
77763	XXX Universal Gun Cleaner	

SEM Products

Rock Hill, SC 29730
Tech Support: 1-800-831-1122
Customer Care: 1-866-327-7829
semproducts.com

LEARN MORE ABOUT RUST PREVENTER CAVITY WAX AT
semproducts.com/product/rust-preventer-cavity-wax



CHECK LOCAL VOC REGULATIONS TO ENSURE COMPLIANCE OF ALL PRODUCTS IN YOUR AREA. ALWAYS WEAR OSHA REQUIRED (PPE) PERSONAL PROTECTION EQUIPMENT TO ENSURE YOUR SAFETY.