



Rust Preventer Cavity Wax

TECHNICAL DATA SHEET



Check local VOC regulations to ensure compliance of all products in your area.

DESCRIPTION

Rust Preventer Cavity Wax is a semi-transparent, black internal panel compound to restore OEM corrosion protection on inner body panels and cavities.

FEATURES

- Non-hardening
- Sprayable in a 360° pattern
- Superior adhesion
- Tested over 2000hrs salt spray
- Superior wicking and creep

SUITABLE SUBSTRATES/

PROPERLY PREPPED (SEE PREPARATION SECTION)

- Inner body panels
- Cavities
- Channels

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
39573	Rust Preventer Cavity Wax	Amber	24 oz. Aerosol
MIR:	Category ABT .812		
Paintable:	No		

Check local VOC regulations to ensure compliance of all products in your area.

Always wear OSHA required (PPE) Personal Protection Equipment as outlined on the SDS and product label to ensure your safety.

PREPARATION

Clean any accessible areas with SEM Solve or XXX Universal Surface Cleaner and wipe dry.



Check local VOC regulations to ensure compliance of all products in your area.

APPLICATION

Shake can for 1 minute prior to use. Remove cap, attach straw or Rigid 360° Applicator.

Apply 1-2 coats. Change the angle of the Rigid 360° Applicator and vary the depth of the applicator inside the panel to ensure complete coverage.

CLEAN UP

Clean the Rigid 360° Applicator by attaching it to a can of XXX Universal Gun Cleaner or solvent compliant with VOC regulations in your area.

STORAGE

Rust Preventer Cavity Wax should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for Rust Preventer Cavity Wax is 3 years when stored at 40-77°F (4-25°C). Exposure above room temperature will reduce shelf life.

RELATED PRODUCTS

Part:	Product:	Size:
38373	SEM Solve	20 oz Aerosol
38374	SEM Solve	Quart
71360	Rigid 360° Applicator	Kit
77763	XXX Universal Gun Cleaner	20 oz Aerosol
77771	XXX Universal Surface Cleaner	Gallon

Technical Consultation Service

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

Disclaimer:

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate. Users should review the Safety Data Sheet (SDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the SDS and product label are available upon request.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.