

DESCRIPTION

Sure-Coat Cross Linker is an additive for Sure-Coat that increases its durability from the effects of most cleaning chemicals.

FEATURES

- Resists common industrial cleaners
- Perfect for refinishing restaurant seats and medical exam tables
- No change in application
- No pot-life once added

SUITABLE SUBSTRATES

- Sure-Coat

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Size:
16004	Sure-Coat Cross Linker	Clear	4 oz. Tube
Regulatory VOC:		0 g/L	
Actual VOC:		0 g/L	
Freeze thaw stability:		yes	


Use VOC calculator to determine VOC of mixtures. Check local VOC regulations to ensure compliance of all products in your area.

HANDLING AND APPLICATION



PREPARATION:

Refer to Sure-Coat TDS for substrate preparation instructions.



MIXING:

Add 5 mL or 5 g to 1 pint of ready to spray Sure-Coat. Pour **Cross Linker** in while stirring to avoid seeding.



APPLICATION:

Hand stir or shake well for 2-3 minutes to ensure proper mix.
Apply per Sure-Coat directions.

Note: After 48 hours, it is recommended to re-cross link Sure-Coat.



Check local VOC regulations to ensure compliance of all products in your area.



CLEANUP:

Flush spray equipment with warm water until clean. Follow with acetone until all water has been removed.



STORAGE:

Sure-Coat Cross Linker should be stored in a cool, dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **Cross Linker** is 1 year when stored under normal conditions.

RELATED PRODUCTS:

Part:	Product Name:	Size:	
16015	Sure-Coat	Black	1/2 Gallon
16085	Sure-Coat	Silver	1/2 Gallon
16505	Sure-Coat	Red Oxide	1/2 Gallon
16515	Sure-Coat	Indo Yellow	1/2 Gallon
16525	Sure-Coat	Quindo Red	1/2 Gallon
16535	Sure-Coat	Thalo Blue	1/2 Gallon
16545	Sure-Coat	White	1/2 Gallon
16565	Sure-Coat	Thalo Green	1/2 Gallon
16585	Sure-Coat	Bright Red	1/2 Gallon
16595	Sure-Coat	Yellow Oxide	1/2 Gallon
16705	Sure-Coat	High Gloss Clear	1/2 Gallon
16715	Sure-Coat	Satin Gloss Clear	1/2 Gallon
16725	Sure-Coat	Low Luster Clear	1/2 Gallon
16018	Sure-Coat	Black	Pint
16088	Sure-Coat	Silver	Pint
16508	Sure-Coat	Red Oxide	Pint
16518	Sure-Coat	Indo Yellow	Pint
16528	Sure-Coat	Quindo Red	Pint
16538	Sure-Coat	Thalo Blue	Pint
16548	Sure-Coat	White	Pint
16568	Sure-Coat	Thalo Green	Pint
16578	Sure-Coat	Magenta	Pint
16588	Sure-Coat	Bright Red	Pint
16598	Sure-Coat	Yellow Oxide	Pint
16708	Sure-Coat	High Gloss Clear	Pint
16718	Sure-Coat	Satin Gloss Clear	Pint
16728	Sure-Coat	Low Luster Clear	Pint



Check local VOC regulations to ensure compliance of all products in your area.

Technical Consultation Service

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

Disclaimer:

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Safety Data Sheet (SDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the SDS and product label are available upon request.